

表1 . SUSパネ材(SUS304-CSP・SUS301-CSP等の板材・エッチング材・コイル材)の
定尺サイズ・板厚寸法公差 (単位:mm)

板厚 mm	板材 (1)	コイル材								エッチング材 (2)	
	SUS304 SUS301	SUS304				SUS301				SUS631	SUS304 SUS301
	調質記号	調質記号				調質記号				調質記号	調質記号
	H 3/4H 1/2H	H	3/4H	1/2H	EH	H	3/4H	1/2H	3/4H	H	
0.01	-	±0.002	-	-	-	-	-	-	-	-	
0.02	-	±0.002	-	-	-	-	-	-	-	-	
0.03	-	±0.003	-	-	-	-	-	-	-	-	
0.04	-	±0.003	-	-	-	-	-	-	-	-	
0.05	-	±0.004	-	-	-	-	-	-	-	-	
0.06	-	±0.004	-	-	-	-	-	-	-	-	
0.07	-	±0.004	-	-	-	-	-	-	-	-	
0.08	-	±0.005	-	-	-	-	-	-	-	±0.005	
0.1	±0.004	±0.004	±0.004	±0.004	±0.004	±0.004	±0.004	±0.004	±0.005	±0.004	
0.12	-	±0.005	±0.005	±0.005	-	-	±0.005	-	-	±0.005	
0.13	-	±0.005	-	-	-	±0.005	±0.005	-	±0.005	±0.005	
0.15	±0.006	±0.006	±0.006	±0.006	±0.006	±0.006	±0.006	±0.006	±0.006	±0.006	
0.18	-	±0.008	±0.008	-	-	-	±0.008	-	±0.008	±0.008	
0.2	±0.008	±0.008	±0.008	±0.008	±0.008	±0.008	±0.008	±0.008	±0.008	±0.008	
0.25	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	
0.3	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	±0.01	
0.35	-	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	-	
0.4	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	±0.012	
0.45	-	±0.018	±0.018	±0.018	-	±0.018	±0.018	±0.018	±0.018	-	
0.5	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.01 -0.02	+0.012 -0.02	+0.01 -0.02	
0.6	+0.012 -0.024	+0.012 -0.024	+0.012 -0.024	+0.012 -0.024	-	+0.012 -0.024	+0.012 -0.024	+0.012 -0.024	+0.012 -0.024	+0.012 -0.024	
0.7	+0.016 -0.028	+0.016 -0.028	+0.016 -0.028	+0.016 -0.028	-	+0.016 -0.028	+0.016 -0.028	+0.016 -0.028	+0.016 -0.028	-	
0.8	+0.016 -0.032	+0.016 -0.032	+0.016 -0.032	+0.016 -0.032	-	+0.016 -0.032	+0.016 -0.032	+0.016 -0.032	+0.016 -0.032	-	
1.0	+0.02 -0.04	+0.02 -0.04	+0.02 -0.04	+0.02 -0.04	-	+0.02 -0.04	+0.02 -0.04	+0.02 -0.04	+0.02 -0.04	-	
1.2	+0.024 -0.048	+0.024 -0.048	+0.024 -0.048	+0.024 -0.048	-	+0.024 -0.048	+0.024 -0.048	+0.024 -0.048	+0.024 -0.048	-	
1.5	+0.03 -0.06	+0.03 -0.06	+0.03 -0.06	+0.03 -0.06	-	+0.03 -0.06	+0.03 -0.06	+0.03 -0.06	-	-	
2.0	SUS304のみ在庫	+0.04 -0.08	+0.04 -0.08	+0.04 -0.08	-	-	-	-	-	-	

- (1) 板材の定尺寸法は、通常、「幅320mm×長さ1000mm」。
ただし、幅については 300mm～325mmの場合もあり。
- (2) エッチング材の定尺寸法は、「幅300mm×長さ500mm」、若しくは「幅600mm×長さ700mm」。
- (3) 「-」表示のものは、通常在庫ではありません。